

# Traffic Controllers for Traffic Operations

## ASC/3 2070

---

### What, exactly, is the ASC/3 2070?

Designed using the latest software development technologies, the ASC/3-2070 software provides an updated robust design that serves as the traffic control platform for present and future traffic management environments. It is compliant with NEMA TS2 and National Transportation Communications for ITS Protocols (NTCIP) standards.

### Why do agencies use ASC/3 2070?

The ASC/3-2070 software offers transportation agencies a controller package that is affordable, reliable, flexible, and is compatible with any pre-qualified 2070 controller, as well as with all existing Econolite systems. ASC/3-2070 is stored in flash memory, allowing quick and easy software updates in the field without changing hardware.

### How does the ASC/3 2070 benefit the driving public?

ASC/3-2070 software improves traffic control capabilities, and with its ease-of-use helps ensure that transportation agencies can provide the safest and most efficient intersections for its driving public. It is also designed with the future in mind, supporting the demands of advanced traffic management and ITS programs.





## Control features

- 16 phases with 8 configurable concurrent groups in 4 timing rings
- All standard NEMA TS1, TS2, and NTCIP functions
- 16 timed vehicle overlaps
- 16 pedestrian phases that can be configured as pedestrian overlaps
- Exclusive pedestrian operation
- Soft vehicle recall
- Conditional service
- Dynamic max operation
- Bike minimum green, second walk and pedestrian clear times, in addition to a walk and pedestrian clearance maximum
- Advanced walk
- Pedestrian clear protect
- Red maximum
- Vehicle extension 2
- Guaranteed minimum green, walk, ped clear, yellow, red, red revert, and overlap green
- Redundant monitoring of the Malfunction Management Unit (MMU) status to enhance intersection monitoring
- 4 timing plans selectable on Time-of-Day (TOD) or coordination plan basis or for one cycle following preemption
- Powerful logic processor

## Coordinator features

- 120 coordination patterns, each with its own cycle, offsets, and split plan selection
- 120 split plans, each with its own coordinated phases, vehicle, and pedestrian recall and phase omits
- Offset and split entries displayed in percent or seconds
- Automatic permissive periods
- Fixed or floating force-off
- Crossing arterial coordination
- Quick-sync feature

## Basic Specifications

- Preemptor features
  - 10 preemption sequences. Each may be configured as priority, first-come-first-serve, or bus preemption operation
  - ECPI dual-circuit preempt interlock to provide added monitoring safety
- Logging features
  - Separate buffers for detector activity, detector failures, controller events, and MMU events
  - Logged data can be viewed on front panel, retrieved via RS-232 terminal port, or transferred via telemetry to a traffic management center
  - Option available to operate with the Linux operating system on a 2070-1C CPU

## Detector features

- 64 vehicle detectors
- 16 system or speed detectors
- Unique detector types and operations
- Individually assignable to phase and functions
- Lock/non-lock function by detector
- 4 detector plans
- 4 detector diagnostic plans
- Logging of volume and/or occupancy assignable by detector
- 4 pedestrian diagnostic plans

